Package: TSGenerator (via r-universe)

October 24, 2026

Title 'Copernicus' HR-VPP Vegetation Time-Series Processing

Version 2.0.1

Description Provides tools for acquiring, extracting, quality-assessing, and analysing vegetation time series derived from 'Copernicus' High Resolution Vegetation Phenology and Productivity (HR-VPP) products. Supports Seasonal Trajectories (ST) and Vegetation Phenology and Productivity (VPP) products through native R access to 'WEkEO', geospatial processing, product-quality assessment, temporal completeness analysis, missingness modelling, and integrated graphical workflows. Selected functions from 'TSGenerator' 1.x are retained to support migration and legacy workflows.

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

URL https://github.com/avalero92/TSGenerator

BugReports https://github.com/avalero92/TSGenerator/issues

Imports hdar, jsonlite, stringr, utils, ggplot2, mgcv, scales, shiny, shinydashboard, shinyjs, shinycssloaders, DT, readr, terra

Suggests imputeTS, knitr, rmarkdown, sf, testthat (>= 3.0.0)

VignetteBuilder knitr

Config/testthat/edition 3

Config/pak/sysreqs cmake libgdal-dev gdal-bin libgeos-dev make libicu-dev libuv1-dev libssl-dev libproj-dev libsqlite3-dev libx11-dev zlib1g-dev

Repository https://avalero92.r-universe.dev

Date/Publication 2026-10-24 14:39:59 UTC

RemoteUrl https://github.com/avalero92/tsgenerator

RemoteRef HEAD

RemoteSha d9b6d3ad2c85a03e0345d9e75687137753f6b150

Contents

assess_ts_quality . . . 3
check_wekeo . . . 3
check_wekeo_integration . . . 4
classify_quality . . . 5
count.NA . . . 6
count_missing . . . 6
Download.HRVPP . . . 7
Download.STPPI . . . 8
Download.VI . . . 8
download_st . . . 9
download_vpp . . . 10
extract_dates_from_tiff_files . . . 11
extract_ts . . . 11
extract_vpp . . . 12
GAM.missing . . . 13
GAM.plot . . . 14
general.Quality . . . 15
geospatial_plan . . . 15
get.Clean.IV . . . 16
get.Series.mean . . . 17
get.Series.median . . . 17
get.Series.VPP . . . 18
get.Stack . . . 18
hda_auth_check . . . 19
hda_client . . . 19
hda_datasets . . . 20
hda_download . . . 21
hda_query_template . . . 21
hda_search . . . 22
impute_ts . . . 23
mask_quality . . . 23
model_missingness . . . 24
plot_missingness . . . 25
QFLAG2.Mask . . . 25
quality.Series . . . 26
quality_info . . . 26
renames.image.IV . . . 27
renames.image.VPP . . . 28
runTSapp . . . 28
summarize_missingness . . . 29
summarize_quality . . . 30
temporal_plan . . . 30
TsImpute . . . 31

Index **33**

assess_ts_quality *Assess time-series completeness quality*

Description

Classifies time-series completeness from the proportion of expected dates containing usable values. This metric is separate from Copernicus ST/VPP QFLAG product quality.

Usage

```
assess_ts_quality(
  data, id_col = "ID", date_col = "Date", value_col = "Value",
  expected_step = NULL, window_days = NULL,
  thresholds = c(high = 0.90, medium = 0.75, low = 0.50),
  start = NULL, end = NULL
)
```

Arguments

`data`	Input time-series data frame.
`id_col`, `date_col`, `value_col`	Column names identifying the series, observation date, and value.
`expected_step`	Expected temporal step in days; if `NULL`, it is inferred when possible.
`window_days`	Optional assessment-window length in days.
`thresholds`	Named completeness thresholds used to assign quality classes.
`start`, `end`	Optional start and end dates restricting the assessment period.

Value

An object of class `tsg_ts_quality` (also a `data.frame`) with one row per series and assessment window. It contains the completeness columns documented in `summarize_missingness()`, a numeric `window` index, and an ordered factor `Quality` with levels `Very low`, `Low`, `Medium`, and `High`, based on `value_completeness`. Attributes `thresholds` and `window_days` record the assessment settings.

check_wekeo *Check the TSGenerator WEkEO acquisition environment*

Description

Performs non-destructive checks of the native R acquisition stack. Offline checks are the default.

Usage

```
check_wekeo(client = NULL, online = FALSE)
```

Arguments

client	Optional client created by hda_client().
online	Logical; perform live WEkEO authentication and schema checks.

Value

A data frame of diagnostic checks with class tsg_wekeo_check.

See Also

hda_client, download_st, download_vpp

---

check_wekeo_integration

Run a live WEkEO integration smoke test

Description

Performs authentication, live schema discovery, small ST/VPP searches and, optionally, download/readability checks.

Usage

```
check_wekeo_integration(
  client = NULL,
  st_tile = "32TPS",
  vpp_tile = "30TXR",
  st_start = "2018-03-01",
  st_end = "2018-03-11",
  vpp_start = "2018-01-01",
  vpp_end = "2018-12-31",
  vpp_product = "TPROD",
  vpp_season = "s1",
  download = FALSE,
  output_dir = NULL,
  quiet = FALSE
)
```

Arguments

client	Optional client created by hda_client().
st_tile	Sentinel-2 MGRS tile used for the ST smoke test.
vpp_tile	Sentinel-2 MGRS tile used for the VPP smoke test.
st_start, st_end	Small ST date range.

`vpp_start`, `vpp_end`
: VPP date range.

`vpp_product`
: VPP parameter used for the smoke test.

`vpp_season`
: VPP season (`"s1"` or `"s2"`).

`download`
: Logical. Search only by default; optionally download matching files.

`output_dir`
: Explicit destination required when downloading; no default directory is created.

`quiet`
: Logical; suppress progress messages.

Value

A list of class `tsg_wekeo_integration`.

`classify_quality` *Decode HR-VPP quality codes*

Description

Decodes HR-VPP quality codes while retaining their categorical meaning.

Usage

```
classify_quality(values, type = c("ST", "VPP"))
```

Arguments

`values`
: Numeric or integer quality codes.

`type`
: Quality-flag family: `"ST"` or `"VPP"`.

Value

A data frame with code, class, rank, default acceptance, and definition.

See Also

`quality_info`, `summarize_quality`, `mask_quality`

count.NA — *Count missing observations (legacy name)*

Description

Retired TSGenerator 1.x compatibility wrapper. Calling this function produces a deprecation warning followed by a migration error. Use `summarize_missingness()` instead.

Usage

```
count.NA(
  data, sos, maxd, eos, doy_col = "DOY", year_col = "Year",
  na_col = "NDVI", fid_col = "ID"
)
```

Arguments

`data`	Input data frame.
`sos`, `maxd`, `eos`	Phenological day-of-year boundaries.
`doy_col`, `year_col`, `na_col`, `fid_col`	Column names for day of year, year, assessed value, and feature identifier.

Value

No return value. This retired compatibility function signals an error with migration guidance; use `summarize_missingness()` instead.

count_missing — *Legacy phenology-specific missing-count interface*

Description

Retired TSGenerator 1.x interface. The former phenology-specific missing-count workflow is no longer executed.

Usage

```
count_missing(
  data, sos, maxd, eos, doy_col = "DOY", year_col = "Year",
  na_col = "NDVI", fid_col = "ID"
)
```

Arguments

`data`	A data frame containing the time series.
`sos`, `maxd`, `eos`	Day-of-year thresholds.
`doy_col`, `year_col`, `na_col`, `fid_col`	Column names.

Value

No return value. This retired function signals an error with migration guidance; use `summarize_missingness()` for missingness counts and `assess_ts_quality()` for completeness classes.

`Download.HRVPP` *Legacy wrapper for VPP download*

Description

Deprecated TSGenerator 1.x compatibility wrapper. It delegates to `download_vpp()` using the native R/hdar backend and no longer requires Python.

Usage

```
Download.HRVPP(
  user = NULL, password = NULL, dataset_id = .VPP_DATASET_ID,
  productType = "SOSD", productGroupId = "s1", tileId = NULL,
  start, end, bbox = NULL, download_path = NULL
)
```

Arguments

`user`, `password`	Optional legacy WEkEO credentials. Current workflows should use the native authentication configuration.
`dataset_id`	Legacy WEkEO dataset identifier.
`productType`	VPP product type.
`productGroupId`	VPP season/product group identifier.
`tileId`	Optional MGRS tile identifier.
`start`, `end`	Start and end dates of the search interval.
`bbox`	Optional bounding box.
`download_path`	Explicit destination required for downloads; no default directory is created.

Value

A `tsg_vpp_download` object.

Download.STPPI — *Legacy wrapper for Seasonal Trajectories download*

Description

Deprecated TSGenerator 1.x compatibility wrapper. It delegates to `download_st()` using the native R/hdar backend and no longer requires Python.

Usage

```
Download.STPPI(
  user = NULL, password = NULL, dataset_id = .ST_DATASET_ID,
  productType = "PPI", platformSerialIdentifier = "S2A, S2B",
  tileId = NULL, start, end, bbox = NULL, download_path = NULL
)
```

Arguments

`user`, `password`	Optional legacy WEkEO credentials. Current workflows should use the native authentication configuration.
`dataset_id`	Legacy WEkEO dataset identifier.
`productType`	Seasonal Trajectories product type.
`platformSerialIdentifier`	Sentinel-2 platform identifier(s).
`tileId`	Optional MGRS tile identifier.
`start`, `end`	Start and end dates of the search interval.
`bbox`	Optional bounding box.
`download_path`	Explicit destination required for downloads; no default directory is created.

Value

A `tsg_st_download` object.

Download.VI — *Discontinued legacy VI downloader*

Description

The HR-VPP VI products targeted by the TSGenerator 1.x downloader are no longer disseminated. This compatibility function stops with migration guidance.

Usage

```
Download.VI(...)
```

Arguments

...	Ignored legacy arguments, retained only for compatibility.

Value

No value; the function raises an error.

---

download_st — *Download Copernicus HR-VPP Seasonal Trajectories*

Description

Searches and optionally downloads HR-VPP Seasonal Trajectories through WEkEO HDA V2 using the native R **hdar** backend.

Usage

```
download_st(start, end, output_dir = NULL, product = "PPI",
  tile_id = NULL, bbox = NULL, platform = "S2A, S2B", resolution = 10L,
  product_version = NULL, client = NULL, download = TRUE, limit = NULL,
  overwrite = FALSE, prompt = interactive(), quiet = FALSE, retries = 2L,
  backoff = 2)
```

Arguments

`start`, `end`	Start and end dates of the WEkEO search interval.
`output_dir`	Explicit destination required when `download = TRUE`; no default directory is created. Ignored in preview mode.
`product`	Seasonal Trajectories product type.
`tile_id`	Optional MGRS tile identifier.
`bbox`	Optional bounding box used to spatially restrict the query.
`platform`	Sentinel-2 platform identifier(s).
`resolution`	Requested spatial resolution in metres.
`product_version`	Optional HR-VPP product version.
`client`	Optional preconfigured native HDA client.
`download`	Logical; download results when `TRUE`, otherwise return a preview.
`limit`	Optional maximum number of search results.
`overwrite`	Logical; overwrite existing files.
`prompt`	Logical; allow interactive download confirmation.
`quiet`	Logical; suppress progress messages when possible.
`retries`	Number of download retries.
`backoff`	Backoff interval used between retries.

Value

An object of class `tsg_st_download`.

`download_vpp` *Download Copernicus HR-VPP VPP parameters*

Description

Searches and optionally downloads HR-VPP phenology and productivity parameters through WEkEO HDA V2 using the native R **hdar** backend.

Usage

```
download_vpp(start, end, output_dir = NULL,
  product = c("SOSD", "MAXD", "EOSD", "LENGTH"), season = "s1",
  tile_id = NULL, bbox = NULL, platform = "S2A, S2B", product_version = NULL,
  client = NULL, download = TRUE, limit = NULL, overwrite = FALSE,
  prompt = interactive(), quiet = FALSE, retries = 2L, backoff = 2)
```

Arguments

`start, end`	Start and end dates of the WEkEO search interval.
`output_dir`	Explicit destination required when `download = TRUE`; no default directory is created. Ignored in preview mode.
`product`	VPP parameter or parameters to query.
`season`	VPP season identifier.
`tile_id`	Optional MGRS tile identifier.
`bbox`	Optional bounding box used to spatially restrict the query.
`platform`	Sentinel-2 platform identifier(s).
`product_version`	Optional HR-VPP product version.
`client`	Optional preconfigured native HDA client.
`download`	Logical; download results when `TRUE`, otherwise return a preview.
`limit`	Optional maximum number of search results.
`overwrite`	Logical; overwrite existing files.
`prompt`	Logical; allow interactive download confirmation.
`quiet`	Logical; suppress progress messages when possible.
`retries`	Number of download retries.
`backoff`	Backoff interval used between retries.

Value

An object of class `tsg_vpp_download`.

extract_dates_from_tiff_files *extract_dates_from_tiff_files*

Description

extract_dates_from_tiff_files

extract_dates_from_tiff_files

extract_dates_from_tiff_files

Usage

```
extract_dates_from_tiff_files(tiff_files)

extract_dates_from_tiff_files(tiff_files)

extract_dates_from_tiff_files(tiff_files)
```

Arguments

`tiff_files`	List of files in .tif format

Value

The names of each of the files in the formats %Y-%m-%d or YYYYYYYMMDD

The names of each of the files in the formats %Y-%m-%d or YYYYYYYMMDD

The names of each of the files in the formats %Y-%m-%d or YYYYYYYMMDD

extract_ts *Extract polygon-level raster time series*

Description

Terra-first replacement for the duplicated TSGenerator 1.x mean and median extraction workflows.

Usage

```
extract_ts(x, polygons, id_col = NULL, fun = "median", dates = NULL,
  transform = TRUE, scale_factor = 1, offset = 0, na.rm = TRUE,
  exact = FALSE, touches = FALSE)
```

Arguments

x	A terra SpatRaster, TIFF path, directory, or vector of TIFF paths.
polygons	An sf/sfc object or terra SpatVector containing polygons.
id_col	Optional unique polygon ID column.
fun	Summary function; mean, median, min, max, sum, or a function.
dates	Optional vector with one date per raster layer.
transform	Transform polygons to raster CRS when needed.
scale_factor	Numeric divisor applied after extraction.
offset	Numeric offset added after scaling.
na.rm	Remove missing raster values during summarisation.
exact	Use exact polygon-cell fractions when supported.
touches	Include cells touched by polygon boundaries.

Value

A tidy data frame of class `tsg_time_series` with ID, Date, Layer and Value columns.

---

extract_vpp *Extract HR-VPP phenology and productivity parameters*

Description

Extracts polygon statistics from Copernicus HR-VPP VPP rasters using product-aware decoding, scaling, NoData handling and season metadata.

Usage

```
extract_vpp(x, polygons, id_col = NULL, product = NULL, season = NULL,
  year = NULL, fun = "median", transform = TRUE, na.rm = TRUE,
  exact = FALSE, touches = FALSE)
```

Arguments

x	VPP raster input, file paths, or directory accepted by TSGenerator.
polygons	Polygon `sf/sfc` object or `terra::SpatVector`.
id_col	Optional polygon identifier column.
product	Optional VPP product filter.
season	Optional season filter.
year	Optional year filter.
fun	Polygon summary function.
transform	Logical; transform polygons to raster CRS when required.
na.rm	Logical; remove missing raster values in summaries.
exact	Logical passed to the extraction backend for exact polygon extraction.
touches	Logical controlling inclusion of touched cells.

Value

A data frame of class `tsg_vpp`. Date products populate `Date`; numeric products populate `Value`.

`GAM.missing` *GAM.missing*

Description

GAM.missing

Usage

```
GAM.missing(data, year_col, doy_col, missing_col)
```

Arguments

`data`	Data frame containing the missingness time-series information.
`year_col`	Name of the column containing years.
`doy_col`	Name of the column containing day-of-year values.
`missing_col`	Name of the column containing the missingness/value indicator used by the legacy wrapper.

Value

A list object where the prediction results and the GAM model data are stored.

Examples

```
# Model fitting is illustrated with synthetic observations.

example_data <- expand.grid(
  Year = 2020:2021, DOY = seq(10, 350, by = 10), replicate = 1:4
)
example_data$NDVI_median <- 0.5
example_data$NDVI_median[
  (seq_len(nrow(example_data)) %% 7L) < 2L
] <- NA_real_
result <- suppressWarnings(GAM.missing(
  example_data, year_col = "Year", doy_col = "DOY",
  missing_col = "NDVI_median"
))
```

GAM.plot *GAM.plot*

Description

GAM.plot

Usage

```
GAM.plot(
  data,
  doy_col = "DOY",
  year_col = "Year",
  proporcion_col = "Proporcion_Missing",
  prediccion_col = "Predicted",
  sos = NULL,
  eos = NULL,
  max_doy = NULL
)
```

Arguments

data	A DataFrame that contains the data to be plotted.
doy_col	Name of the column representing the Julian Day (DOY).
year_col	Name of the column representing the Year.
proporcion_col	Name of the column representing the Proportion of Missing Data.
prediccion_col	Name of the column representing the Prediction.
sos	Optional value for the SOS line.
eos	Optional value for the EOS line.
max_doy	Optional value for the MAX line.

Value

Object of type ggplot that shows the results of the prediction obtained with the GAM.missing function.

Examples

```
proportions <- data.frame(
  Year = rep(2020L, 5), DOY = c(20, 50, 80, 110, 140),
  Proporcion_Missing = c(0.1, 0.2, 0.3, 0.2, 0.1),
  Predicted = c(0.12, 0.18, 0.25, 0.18, 0.12)
)
p <- suppressWarnings(GAM.plot(proportions))
inherits(p, "ggplot")
```

general.Quality — *general.Quality*

Description

general.Quality

Usage

```
general.Quality(df, period_col, observations_col)
```

Arguments

df	Data base generated from the use of the function quality.Series
period_col	Column where the periods are stored (every 91 days)
observations_col	Columna donde se almacenan el numero de observaciones por periodo y

Value

A list of files that stores a new data frame and an interactive graphic.

geospatial_plan — *Inspect inputs for the TSGenerator 2.0 geospatial engine*

Description

Validates raster/vector geometry, CRS, IDs, and scaling before terra-based extraction.

Usage

```
geospatial_plan(
  x, polygons, id_col = NULL, transform = TRUE,
  scale_factor = 1, offset = 0
)
```

Arguments

x	A `terra::SpatRaster`, TIFF path, directory, or vector of TIFF paths.
polygons	An `sf`/`sfc` object or `terra::SpatVector` of polygons.
id_col	Optional unique polygon ID column.
transform	Logical; transform polygons to the raster CRS when required.
scale_factor	Numeric divisor applied after extraction.
offset	Numeric offset applied after scaling.

Value

An object of class `tsg_geospatial_plan`; no extraction is performed.

See Also

`extract_ts`, `extract_vpp`

---

get.Clean.IV *Legacy VI cleaning workflow*

Description

get.Clean.IV() belongs to the discontinued VI/QFLAG2 workflow. It is retained only as a migration guard. Use mask_quality() for current ST/VPP quality handling.

Usage

```
get.Clean.IV(...)
```

Arguments

`...`	Legacy arguments. They are accepted only so existing calls fail with explicit migration guidance.

Value

This function does not return a value; it stops with migration guidance.

Examples

```
## Not run:
get.Clean.IV()

## End(Not run)
```

get.Series.mean — *Legacy mean time-series extractor*

Description

Deprecated compatibility wrapper around `extract_ts(..., fun = "mean")`.

Usage

```
get.Series.mean(pathRaster = NULL, shapefile = NULL, factorR = NULL)
```

Arguments

`pathRaster`	Directory containing TIFF rasters.
`shapefile`	Polygon sf/sfc or terra SpatVector.
`factorR`	Legacy numeric scale divisor.

Value

A data frame with legacy columns ID, Date, and Mean.

get.Series.median — *Legacy median time-series extractor*

Description

Deprecated compatibility wrapper around `extract_ts(..., fun = "median")`.

Usage

```
get.Series.median(pathRaster = NULL, shapefile = NULL, factorR = NULL)
```

Arguments

`pathRaster`	Directory containing TIFF rasters.
`shapefile`	Polygon sf/sfc or terra SpatVector.
`factorR`	Legacy numeric scale divisor.

Value

A data frame with legacy columns ID, Date, and Mean. The historical column name is preserved.

get.Series.VPP — *Retired legacy VPP extractor*

Description

Retired because one generic scale factor is not scientifically valid across VPP products. Use `extract_vpp()`.

Usage

```
get.Series.VPP(pathRaster = NULL, shapefile = NULL, factorR = NULL)
```

Arguments

`pathRaster`	Legacy raster directory.
`shapefile`	Legacy polygon object.
`factorR`	Legacy scale factor.

Value

No return value. This retired function always signals an error explaining the migration to `extract_vpp()`.

get.Stack — *Legacy VI/QFLAG stack workflow*

Description

get.Stack() belongs to the discontinued VI/QFLAG2 workflow. It is retained only as a migration guard; current ST and QFLAG products should remain separate.

Usage

```
get.Stack(...)
```

Arguments

`...`	Legacy arguments. They are accepted only so existing calls fail with explicit migration guidance.

Value

This function does not return a value; it stops with migration guidance.

Examples

```
## Not run:
get.Stack()

## End(Not run)
```

---

hda_auth_check *Test native WEkEO authentication*

Description

Checks that the configured WEkEO credentials can obtain an HDA authentication token.

Usage

```
hda_auth_check(client = NULL, ...)
```

Arguments

client	Optional client created by `hda_client()`.
...	Arguments passed to `hda_client()` when `client` is omitted.

Value

Invisibly returns `TRUE` after a token is obtained.

See Also

`hda_client`, `check_wekeo`

---

hda_client *Create a native WEkEO HDA client*

Description

Creates the native R client used by TSGenerator to access WEkEO HDA. If credentials are omitted, **hdar** uses '`~/.hdarc`'.

Usage

```
hda_client(username = NULL, password = NULL, save_credentials = FALSE)
```

Arguments

`username`	Optional WEkEO username.
`password`	Optional WEkEO password.
`save_credentials`	Logical; allow **hdar** to save credentials in '`~/.hdarc`'.

Value

An authenticated `hdar::Client` object.

See Also

`hda_auth_check`, `check_wekeo`, `download_st`, `download_vpp`

`hda_datasets` *Discover WEkEO datasets*

Description

Queries the WEkEO catalogue through the native HDA client.

Usage

```
hda_datasets(pattern = NULL, client = NULL)
```

Arguments

`pattern`	Optional text used to filter the WEkEO catalogue.
`client`	Optional authenticated HDA client.

Value

Dataset records returned by **hdar**.

See Also

`hda_query_template`

hda_download — *Download HDA search results*

Description

Downloads WEkEO HDA search results with controlled retry behaviour.

Usage

```
hda_download(
  results, output_dir, force = FALSE, retries = 2L,
  backoff = 2, prompt = interactive()
)
```

Arguments

`results`	SearchResults returned by `hda_search()`.
`output_dir`	Destination directory.
`force`	Logical; re-download existing files when supported.
`retries`	Number of retries after transient failures.
`backoff`	Initial retry delay in seconds.
`prompt`	Logical; allow **hdar** to request confirmation.

Value

The value returned by the **hdar** download method, invisibly.

See Also

`hda_search`

hda_query_template — *Generate an HDA V2 query template*

Description

Retrieves the current queryable schema for a WEkEO dataset rather than hard-coding provider-specific query fields.

Usage

```
hda_query_template(dataset_id, client = NULL)
```

Arguments

`dataset_id`	WEkEO dataset identifier.
`client`	Optional authenticated HDA client.

Value

A query template returned by **hdar**.

See Also

`hda_datasets`, `hda_search`

---

hda_search *Search WEkEO using an HDA V2 query*

Description

Submits an HDA V2 search with controlled retry and exponential backoff.

Usage

```
hda_search(query, client = NULL, limit = NULL, retries = 2L, backoff = 2)
```

Arguments

`query`	HDA V2 query, normally based on `hda_query_template()`.
`client`	Optional authenticated HDA client.
`limit`	Optional maximum number of results.
`retries`	Number of retries after transient failures.
`backoff`	Initial retry delay in seconds.

Value

An **hdar** SearchResults object.

See Also

`hda_download`

impute_ts — *Impute missing values in vegetation time series*

Description

Explicit, opt-in imputation with provenance and safeguards for processed Seasonal Trajectories.

Usage

```
impute_ts(data, id_col = "ID", date_col = "Date", value_col = "Value",
  method = c("linear", "kalman"), series_type = c("user", "raw", "st"),
  allow_processed = FALSE, complete_grid = FALSE, expected_step = NULL,
  max_gap = NULL, allow_edge = FALSE, output_col = NULL)
```

Arguments

`data`	Input time-series data frame.
`id_col`, `date_col`, `value_col`	Column names identifying the series, observation date, and value.
`method`	Imputation method.
`series_type`	Series provenance: user, raw, or processed ST.
`allow_processed`	Logical; explicitly permit additional imputation of processed ST series.
`complete_grid`	Logical; complete the expected temporal grid before imputation.
`expected_step`	Expected temporal step in days.
`max_gap`	Optional maximum gap eligible for imputation.
`allow_edge`	Logical; permit filling gaps at series edges where supported.
`output_col`	Optional name for the imputed output column.

Value

A data frame of class `tsg_imputed_series`.

mask_quality — *Mask raster values using HR-VPP quality flags*

Description

Masks values according to explicit quality rules. Categorical QFLAG rasters are never resampled automatically.

Usage

```
mask_quality(
  x,
  quality,
  type = c("ST", "VPP"),
  min_quality = NULL,
  keep_codes = NULL
)
```

Arguments

x	Target terra::SpatRaster.
quality	Quality terra::SpatRaster with matching geometry.
type	Quality-flag family, either "ST" or "VPP".
min_quality	Optional minimum quality code.
keep_codes	Optional explicit quality codes to retain; overrides min_quality.

Value

A masked terra::SpatRaster.

See Also

quality_info, classify_quality

---

model_missingness *Model temporal missingness with a generalized additive model*

Description

Aggregates missing/available counts and fits a binomial GAM. Year is treated as a factor by default.

Usage

```
model_missingness(
  data, year_col = "Year", doy_col = "DOY", value_col = "Value",
  k = NULL, year_effect = c("factor", "none"), cyclic = TRUE
)
```

Arguments

data	Data frame containing repeated observations.
year_col, doy_col, value_col	Column names.
k	Optional GAM basis dimension.
year_effect	Factor year effect or none.
cyclic	Use a cyclic DOY smooth.

Value

An object of class `tsg_missingness_model`.

---

plot_missingness *Plot observed and modelled temporal missingness*

Description

Plots observed missingness proportions and GAM predictions without printing automatically.

Usage

```
plot_missingness(x, sos = NULL, max_doy = NULL, eos = NULL, facet = TRUE)
```

Arguments

`x`	A tsg_missingness_model or compatible data frame.
`sos`, `max_doy`, `eos`	Optional DOY markers.
`facet`	Facet by year.

Value

A ggplot object.

QFLAG2.Mask *Legacy VI QFLAG2 masking workflow*

Description

QFLAG2.Mask() targets the discontinued VI QFLAG2 product. It is retained only as a migration guard. Use quality_info(), summarize_quality(), classify_quality(), and mask_quality() for current ST/VPP quality products.

Usage

```
QFLAG2.Mask(...)
```

Arguments

`...`	Legacy arguments. They are accepted only so existing calls fail with explicit migration guidance.

Value

This function does not return a value; it stops with migration guidance.

Examples

```
## Not run:
QFLAG2.Mask()

## End(Not run)
```

---

quality.Series *quality.Series*

Description

quality.Series

Usage

```
quality.Series(df, id_col, fecha_col, value_col)
```

Arguments

df	Data base
id_col	Column where the observation grid identifiers are located.
fecha_col	Column where the date is located (%yyyyy%mm%dd)
value_col	Column from which the quality of the time series will be determined (estimating the number of observations).

Value

A list of files where a dataframe with the results of the quality assessment and an interactive graphic are stored.

---

quality_info *HR-VPP quality-code definitions*

Description

Returns the TSGenerator definitions used to interpret current HR-VPP ST-QFLAG or VPP-QFLAG values.

Usage

```
quality_info(type = c("ST", "VPP"))
```

Arguments

type	Quality-flag family: "ST" or "VPP".

Value

A data frame describing the supported quality codes and classes.

See Also

classify_quality, summarize_quality, mask_quality

---

renames.image.IV *Legacy VI file renaming helper*

Description

renames.image.IV() belongs to the discontinued VI workflow and is retained only as a migration guard.

Usage

```
renames.image.IV(...)
```

Arguments

...	Legacy arguments. They are accepted only so existing calls fail with explicit migration guidance.

Value

This function does not return a value; it stops with migration guidance.

Examples

```
## Not run:
renames.image.IV()

## End(Not run)
```

renames.image.VPP *renames.image.VPP*

Description

Rename TIF files in a directory according to the year extracted from the name.

Usage

```
renames.image.VPP(...)
```

Arguments

...	Legacy arguments.

Details

This function searches for TIF files in a specified directory and renames them using the year extracted from the filename. The new file name shall be in the format 'yyyy.tif'.

Value

Does not return a value, but renames the TIF files in the specified directory.

runTSapp *Run the TSGenerator graphical interface*

Description

Launches the unified TSGenerator 2.0 Shiny application. Selected 1.x/early-2.0 acquisition mini-apps remain temporarily accessible for compatibility, but new development is concentrated in the unified interface.

Usage

```
runTSapp(app = "TSGenerator2")
```

Arguments

app	Character string. Application to launch. The default, `"TSGenerator2"`, launches the unified 2.0 interface. Compatibility options are `"DownloadSTPPI"` and `"DownloadVPP"`.

Details

The unified application is a graphical layer over the public TSGenerator 2.0 API. Scientific algorithms are not reimplemented in the Shiny server. The historical standalone GAM interface has been retired; missingness modelling remains available through `model_missingness()` and `plot_missingness()`.

Value

Invisibly returns the result of `shiny::runApp()`.

See Also

`model_missingness()`, `plot_missingness()`

Other applications: `runTSapp()`

Examples

```
## Not run:
TSGenerator::runTSapp()
TSGenerator::runTSapp("DownloadVPP")

## End(Not run)
```

---

summarize_missingness *Summarise missingness and temporal completeness*

Description

Separates absent expected dates from explicit NA values and reports temporal and usable-value completeness for each series.

Usage

```
summarize_missingness(
  data, id_col = "ID", date_col = "Date", value_col = "Value",
  expected_step = NULL, start = NULL, end = NULL
)
```

Arguments

`data`	Input time-series data frame.
`id_col`, `date_col`, `value_col`	Column names identifying the series, observation date, and value.
`expected_step`	Expected temporal step in days; if `NULL`, it is inferred when possible.
`start`, `end`	Optional start and end dates restricting the summary period.

Value

An object of class `tsg_missingness` (also a `data.frame`) with one row per series. Columns are the identifier (named by `id_col`), `start`, `end`, `expected_step_days`, `n_expected`, `n_observed_dates`, `n_absent_dates`, `n_value_na`, `n_usable`, `date_completeness`, `value_completeness`, and `missing_fraction`. Counts distinguish absent expected dates from observed dates with missing values. Fractions use `n_expected` as the denominator and are `NA` when that count is zero.

summarize_quality *Summarize HR-VPP quality flags*

Description

Summarizes the distribution of HR-VPP quality flags without masking observations.

Usage

```
summarize_quality(x, type = c("ST", "VPP"), quality_col = "QFLAG")
```

Arguments

x	Quality codes, a `terra::SpatRaster`, or a data frame.
type	Quality-flag family.
quality_col	Column containing codes when `x` is a data frame.

Value

A data frame with counts and percentages by documented quality code.

See Also

`quality_info`, `classify_quality`, `mask_quality`

temporal_plan *Inspect and validate a vegetation time series*

Description

Validates IDs, dates, missing values, duplicate observations, and temporal regularity without modifying the series.

Usage

```
temporal_plan(
  data, id_col = "ID", date_col = "Date", value_col = "Value",
  expected_step = NULL, allow_duplicates = FALSE
)
```

Arguments

`data`	A data frame containing one or more time series.
`id_col`	Series identifier column.
`date_col`	Date column.
`value_col`	Value column.
`expected_step`	Optional expected temporal step in days.
`allow_duplicates`	Logical; allow duplicate ID-date observations.

Value

An object of class `tsg_temporal_plan` containing validated data and diagnostics.

See Also

`summarize_missingness`, `assess_ts_quality`, `impute_ts`

`TsImpute` *TsImpute*

Description

TsImpute

Usage

```
TsImpute(data, group_col, value_col)
```

Arguments

`data`	data frame where VI time series containing missing data are stored.
`group_col`	column by which the grouping is to be performed (example: ID column)
`value_col`	column where the time series of the VI data is stored (example: NDVI)

Value

A new file similar to the original data frame but with a new column where the imputed data is stored.

Examples

```
# Kalman imputation requires the optional imputeTS package.
if (requireNamespace("imputeTS", quietly = TRUE)) {
  example_data <- data.frame(
    ID = rep("parcel_1", 12),
    Date = as.Date("2020-01-01") + 0:11,
    NDVI = c(0.2, 0.3, NA, 0.4, 0.5, NA, 0.6, 0.7, 0.8, 0.7, 0.6, 0.5)
  )
  completed <- suppressWarnings(TsImpute(
    example_data, group_col = "ID", value_col = "NDVI"
  ))
}
```

Index

∗ **WEkEO acquisition**
- check_wekeo, 3
- hda_auth_check, 19
- hda_client, 19
- hda_datasets, 20
- hda_download, 21
- hda_query_template, 21
- hda_search, 22

∗ **applications**
- runTSapp, 28

∗ **geospatial core**
- geospatial_plan, 15

∗ **product quality**
- classify_quality, 5
- mask_quality, 23
- quality_info, 26
- summarize_quality, 30

∗ **time-series analysis**
- temporal_plan, 30

assess_ts_quality, 3, *31*

check_wekeo, 3, *19, 20*
check_wekeo_integration, 4
classify_quality, 5, *24*, *27*, *30*
count.NA, 6
count_missing, 6

Download.HRVPP, 7
Download.STPPI, 8
Download.VI, 8
download_st, *4*, 9, *20*
download_vpp, *4*, 10, *20*

extract_dates_from_tiff_files, 11
extract_ts, 11, *16*
extract_vpp, 12, *16*

GAM.missing, 13
GAM.plot, 14
general.Quality, 15
geospatial_plan, 15
get.Clean.IV, 16
get.Series.mean, 17
get.Series.median, 17
get.Series.VPP, 18
get.Stack, 18

hda_auth_check, 19, *20*
hda_client, *4*, 19, *19*
hda_datasets, 20, *22*
hda_download, 21, *22*
hda_query_template, *20*, 21
hda_search, *21*, 22, *22*

impute_ts, 23, *31*

mask_quality, *5*, 23, *27*, *30*
model_missingness, 24, *29*
model_missingness(), *28*

plot_missingness, 25, *29*
plot_missingness(), *28*

QFLAG2.Mask, 25
quality.Series, 26
quality_info, *5*, *24*, 26, *30*

renames.image.IV, 27
renames.image.VPP, 28
runTSapp, 28

summarize_missingness, 29, *31*
summarize_quality, *5*, *27*, 30

temporal_plan, 30
TsImpute, 31